CERTIFICATE OF COMPLIANCE

Certificate Number	E53006
Report Reference	E53006-20180831
Date	2023-November-17

Issued to:

Westlake Compounds L L C
2801 Post Oak Blvd, Suite # 600
Houston TX, TX 77056 US

This is to certify that representative samples of

PLASTICS - COMPONENT

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety:

"For standard information please visit UL iQ Plastics Database" https://iq.ulprospector.com/en/_?tt=1009

Additional Information:

See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.

Deborah Jennings-Conner

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number	E53006
Report Reference	E53006-20180831
Date	2023-November-17

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Polyvinylchloride (PVC), Material Designation: 5009, GG-5009, 6597(f1), HF-6597(f1), 7140 (f1)

INDEX TO FOOTNOTES:

- PTI @ 175 V - Pass.
(a) - ASTM E-162 (RP-42) : Flame Spread Index: less than 50; Sustained flaming: 9 in.; Dripping: No.
(b) - ASTM E-162 (RP-10) : Flame Spread Index: less than 10; Sustained flaming: 9 in.; Dripping: No.
(c) - ASTM E-162 (RP-47) : Flame Spread Index: less than 50; Sustained flaming: 9 in.; Dripping: No.
(d) - ASTM E-162 (RP-35) : Flame Spread Index: less than 35; Sustained flaming: 9 in.; Dripping: No.
(e) - ASTM D 150-11 Permittivity of 18 @ 1.0MHz, Dissipation Factor 0.010uS
(f) - ASTM D 150-11 Permittivity of 19 @ 1.0MHz, Dissipation Factor 0.018uS
(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.
(f2) - Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL.
(g) - Surface Resistivity 10E14
(h) - Surface Resistivity 10E15

Deborah Jennings-Conner

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/